

AD-A275 872

MML TM 94-02

COLLOCATED TUNABLE WAVENUMBER SENSOR/ACTUATORS FOR SMART STRUCTURES

N00014-92-C-0214

CDRL A001.16

Covering the period: 1 January to 31 January 1994

Submitted to:

Office of Naval Research Scientific Officer Code: 1221

Submitted by:

K. Bridger L. Jones S FLECTE PEB 18 1994 E

MARTIN MARIETTA CORPORATION

Martin Marietta Laboratories 1450 South Rolling Road Baltimore, Maryland 21227-3898 (410) 204-2000

February 7, 1994

DTIC QUALITY INSPECTED !



8P | 9405377

Contract progress and activities since CDRL A001.15.

Summary of progress

Two actuator modules have just come out of burnout. This burnout took longer than anticipated due to power outages during January.

The measurements on the smaller actuators have been repeated and agreed with the

previously reported values within ±10%.

Measurements made on a glued stack showed stiffening with increasing stress from a modulus of about 4 Mpsi at 1000 psi to 12 Mpsi at 10,000 psi applied stress -- this shows the advantage of the cofired actuator.

Telephone calls, trips, and significant results

Bridger briefed Commander Polcari (PEO, ASTO), Ken Dial and representatives of the Navy Labs, transducer community on the use of PMN in transducers. Data from this contract were included and acknowledged.

At 3000 psi prestress the small actuators delivered 350 ustrain at 22°C corresponding to a thrust of approximately 11,000 lb from the full-scale module -- the strain will be much greater at

sea-water temperatures.

Results bearing on prior problem areas

None

Programmatic changes

None

Technical or scheduling problem areas

None

Contract and cost schedule status

Expended funds as of 30 January 1994, including expenditures prior to 23 July, were \$221K against a current budget of \$240K -- the change from last month resulted from adjusting the budget to allow for the lack of funds for the final increment.

A revised cost schedule, beginning at the 23 July program restart, and reflecting the \$114K

funding gap is attached.

Plans for February 1994

Electromechanical measurements will be conducted on an actuator over the temperature range of interest (0-30°C)

The two actuator modules just out of burnout will be sintered.

The fifth and what should be final burnout iteration will be started.

Preparers

Dr. Keith Bridger,

Ms. Lori Jones.

Program Manager

Principle Investigator

(410) 204-2229

(email: BRiDGER@mml.mmc.com


(410) 204-2223

(410) 204-2100

FAX

	Accesion For			
	NTIS	CRA&I		
Į	DTIC	TAB 📋		
	Unannounced			
)	Justification A 27470			
	Ву			
	Distribution/			
Availability Codes				
Dist		Avail and/or		
	וטואנ	Special		
	12-1			

SCHEDULE, MILESTONES, AND DELIVERABLES -- Updated February 5, 1994




KEY:	
Milestone:	Δ
Planned task:	
Completed task:	
Task with new projected completion:	

ONR Sch Miles Deliv Ph-I

Feb 7, 1994

EXPENDITURE CHART

3117-000 ONR Co-Fired High-Force Actuators



AMOUNT EXPENDED (\$K)

AMOUNT EXPENDED (\$K)

MML TM 94-02

COLLOCATED TUNABLE WAVENUMBER SENSOR/ACTUATORS FOR SMART STRUCTURES

N00014-92-C-0214

CDRL A001.16

Covering the period: 1 January to 31 January 1994

Submitted to:

Office of Naval Research Scientific Officer Code: 1221

Submitted by:

K. Bridger L. Jones

MARTIN MARIETTA CORPORATION
Martin Marietta Laboratories
1450 South Rolling Road
Baltimore, Maryland 21227-3898
(410) 204-2000

February 7, 1994

Contract progress and activities since CDRL A001.15.

Summary of progress

- Two actuator modules have just come out of burnout. This burnout took longer than anticipated due to power outages during January.
- The measurements on the smaller actuators have been repeated and agreed with the previously reported values within +10%.
- Measurements made on a glued stack showed stiffening with increasing stress from a modulus of about 4 Mpsi at 1000 psi to 12 Mpsi at 10,000 psi applied stress -- this shows the advantage of the cofired actuator.

Telephone calls, trips, and significant results

- Bridger briefed Commander Polcari (PEO, ASTO), Ken Dial and representatives of the Navy Labs. transducer community on the use of PMN in transducers. Data from this contract were included and acknowledged.
- At 3000 psi prestress the small actuators delivered 350 µstrain at 22°C corresponding to a thrust of approximately 11,000 lb from the full-scale module -- the strain will be much greater at sea-water temperatures.

Results bearing on prior problem areas

None

Programmatic changes

None

Technical or scheduling problem areas

None

Contract and cost schedule status

- Expended funds as of 30 January 1994, including expenditures prior to 23 July, were \$221K against a current budget of \$240K -- the change from last month resulted from adjusting the budget to allow for the lack of funds for the final increment.
- A revised cost schedule, beginning at the 23 July program restart, and reflecting the \$114K funding gap is attached.

Plans for February 1994

- Electromechanical measurements will be conducted on an actuator over the temperature range of interest (0-30°C)
- The two actuator modules just out of burnout will be sintered.
- The fifth and what should be final burnout iteration will be started.

Preparers


Dr. Keith Bridger, Program Manager (410) 204-2229

(email: BRIDGER@mml.mmc.com)

Ms. Lori Jones, Principle Investigator (410) 204-2223

(410) 204-2100 FAX

SCHEDULE, MILESTONES, AND DELIVERABLES -- Updated February 5, 1994




KEY:	
Milestone:	Δ
Planned task:	
Completed task:	
Task with new projected completion:	

ONR Sch Miles Deliv Ph-I

Feb 7, 1994

EXPENDITURE CHART

3117-000 ONR Co-Fired High-Force Actuators



AMOUNT EXPENDED (\$K)

AMOUNT EXPENDED (\$K)